# **Attention HVAC Wholesalers!**

Tork Timers now available exclusively from Robertshaw.



# **SPECIFICATION SHEET**

TU40 SERIES
UNIVERSAL MULTI-VOLTAGE
ELECTROMECHANICAL
24 HOUR TIME SWITCH

#### **APPLICATIONS**

- Pumps motors fans
- Signs and lighting
- Water Heaters
- Heating and air conditioning

## **FEATURES**

- Automatic input voltage detection
  - No DIP switch settings
- 24 hour real time clock face
  - Captive trippers
  - Minimum setting 15 minutes
- 4 in 1 DPDT contacts include SPST, SPDT, DPST
- Load ON Red LED indicator
- Power On Green LED indicator
- ON/OFF/AUTO Switch

#### **SPECIFICATIONS**

MULTI-VOLTAGE INPUT (automatic detection):

120/208-240/277VAC

**OPERATING TEMPERATURE:** 

-31°F to 116°F (-35°C to +47°C)


TERMINAL RANGE: #8 - #18AWG
POWER CONSUMPTION: 6VA Max
ENCLOSURE: Indoor/Outdoor NEMA
3R plastic is standard or NEMA 1 metal

case (with suffix -Y) **DIMENSIONS:** 


NEMA 3R - 8 5/16" x 5 1/16" x 3 1/6" NEMA 1 - 7 15/16" x 4 11/16" x 2 15/16"

# **WIRING DIAGRAM**

### 120/277VAC Application



#### 208/240VAC Application



CATALOG NO.	UPC CODE	TIMER SUPPLY (VAC) 60Hz	ENCLOSURE Type	DRY CONTACTS (UNPOWERED)
TU40	24000	120/208-240/277	NEMA 3R	DPDT
TU40-Y	24001	120/208-240/277	NEMA 1	DPDT

	CONTACT RATING			
TYPE	VOLTAGE	RATING		
		NO	NC	
General Purpose	120-277VAC	40A	30A	
Inductive	120-277VAC	30A	15A	
Ballast	120VAC	30A	10A	
Dullusi	277VAC	20A	10A	
Tungsten	120VAC	15A		
luligateli	250VAC	5A		
Motor Load	120VAC	1HP, 30FLA, 90LRA	¼HP, 12FLA, 30LRA	
MOIOI LOUU	240VAC	2HP, 20FLA, 60LRA	1/2HP, 12FLA, 33LRA	
Pilot Duty	120VAC	720VA	290VA	
Thoi Doly	240VAC	720VA	360VA	
Resistive	28VDC	20A		
Max above 104°F	120-277VAC	30A		



