

ETC Series

Electronic Controls



Description

The Ranco® ETC Series Electronic Temperature Control offers a full featured electronic replacement for electrical-mechanical temperature controls used in many commercial refrigeration applications. With its wide temperature range, one and two stage capability, selectable heating/cooling modes and multi-voltage input, the ETC is designed to provide application flexibility. Models available include 120/208/240V AC and 24V AC.

Features and Benefits

- Wide temperature range -30°F to 220°F (-34,4°C to 104,4°C)
- Wide differential adjustment 1°F to 30°F (-17°C to -1°C)
- LCD read-out for sensor temperature, control settings and relay status
- High Amp output relay (FLA 16 Amps @ 120V AC and 8 Amps @ 208/240V AC) single stage
- EEPROM memory retains control settings during power outages
- Keypad lockout to prevent end-user alteration of settings
- 8 foot lead with sensor is extendable up to 400 feet using 18 or 22-gauge thermostat wire
- Easy 4-step set-up
- Heavy-duty relay is 1 HP rated
- Selectable °F or °C heating/cooling modes
- Single and two stage models
- NEMA 1 case and cover
- NEMA 4X models available
- White backlight on display
- Sensor rated IP67 for dust and water (<1m) resistance



Robertshaw
RANCO • PARAGON • CASTFUTURA

Customer Service
+1 800 304 6563
HVACCustomerService
@robertshaw.com

Technical Service
+1 800 445 8299
TechnicalService
@robertshaw.com

www.robertshaw.com
©2024 Robertshaw
07/24 150-2661 RevB

Specifications

Part Numbers	Description	Number of Stages	Enclosure Type	Temperature Range	Differential Range	Electrical Rating	0 to 10 Volt Output
ETC-111000-000	Electronic Temperature Control	One	NEMA 1	-30°F to 220°F (-34°C to 104°C)	1°F to 30°F (1°C to 16°C)	120/208/240V AC	No
ETC-111100-000	Electronic Temperature Control	One	NEMA 1	-30°F to 220°F (-34°C to 104°C)	1°F to 30°F (1°C to 16°C)	120/208/240 V AC	Yes
ETC-112000-000	Electronic Temperature Control	One	NEMA 1	-30°F to 220°F (-34°C to 104°C)	1°F to 30°F (1°C to 16°C)	24V AC	No
ETC-112100-000	Electronic Temperature Control	One	NEMA 1	-30°F to 220°F (-34°C to 104°C)	1°F to 30°F (1°C to 16°C)	24V AC	Yes
ETC-141000-000	Electronic Temperature Control	One	NEMA 4X	-30°F to 220°F (-34°C to 104°C)	1°F to 30°F (1°C to 16°C)	120/208/240 V AC	No
ETC-211000-000	Electronic Temperature Control	Two	NEMA 1	-30°F to 220°F (-34°C to 104°C)	1°F to 30°F (1°C to 16°C)	120/208/240 V AC	No
ETC-211100-000	Electronic Temperature Control	Two	NEMA 1	-30°F to 220°F (-34°C to 104°C)	1°F to 30°F (1°C to 16°C)	120/208/240 V AC	Yes
ETC-212000-000	Electronic Temperature Control	Two	NEMA 1	-30°F to 220°F (-34°C to 104°C)	1°F to 30°F (1°C to 16°C)	24V AC	No
ETC-212100-000	Electronic Temperature Control	Two	NEMA 1	-30°F to 220°F (-34°C to 104°C)	1°F to 30°F (1°C to 16°C)	24V AC	Yes
ETC-241000-000	Electronic Temperature Control	Two	NEMA 4X	-30°F to 220°F (-34°C to 104°C)	1°F to 30°F (1°C to 16°C)	120/208/240 V AC	No
1309007-044	Thermistor Sensor, 2" long x 1/4" diameter with 8' #22 AWG cable	NA	NA	NA	NA	NA	NA

Relay Electrical Ratings

Single Stage Models			Two Stage Models	
120V AC	208/240V AC	NO Contact	120V AC	208/240V AC
16 Amps	8 Amps	Full-load Amps	9.8 Amps	4.9 Amps
96 Amps	48 Amps	Locked Rotor Amps	58.8 Amps	29.4 Amps
15 Amps	8 Amps	Resistive Amps	9.8 Amps	4.9 Amps
1 HP	1 HP	Horsepower	1/2 HP	1/2 HP
120V AC	208/240V AC	NC Contact	120V AC	208/240V AC
5.8 Amps	2.9 Amps	Full-load Amps	5.8 Amps	2.9 Amps
34.8 Amps	17.4 Amps	Locked Rotor Amps	34.8 Amps	17.4 Amps
5.8 Amps	2.9 Amps	Resistive Amps	5.8 Amps	2.9 Amps
1/4 HP	1/4 HP	Horsepower	1/4 HP	1/4 HP