

G8 SERIES TOP BURNERS

The Robertshaw[®] G8 Series Top Burners are designed as a standard burner system with customization options. OEMs can scale the burner system to a wide range of appliance price ranges with minimal changes to the appliance.

Features and Benefits

- Sealed burner construction
- Primary air from below the cooktop
- Four physical sizes with burner ratings of:
 - 5,000 BTU
 - 9,500 BTU
 - 12,000 to 15,000 BTU
 - 17,000 to 20,000 BTU
- Removable or attached burner head
- Bottom feed orifice holder with rail mounting legs electrode mounts to the orifice holder and is accessible from the top of the appliance
- Bottom feed orifice holder includes a staked tube for easy valve connection
- Side feed orifice holder for shallow burner box applications electrode mounts to the burner head
- Burner can be used as standard ignition or re-ignition without changing any components
- Nominal turndown performance: 10:1
- Burner head material: Die cast aluminum (A380) or Brass

Specifications (Customizable Options)

- Burner skirt
 - Large (tall or short) or Small skirt
 - Polished or standard blast finish
 - Premium blast finish
- Burner cap
 - Sheet metal with enamel finish
 - Powdered metal (PM) with enamel finish
- Ignition: standard or re-ignition (same burner and ignitor for both)







G8 SERIES TOP BURNERS

PRODUCT DIMENSIONS



