

RS9423T

Programmable Thermostat
Multi-Stage – 4 Heat / 2 Cool

Robertshaw



Description

Contractors can offer owners easy, yet powerful and reliable multi-stage temperature control in a simple, modern design with the RS9423T programmable wall thermostat.

Features and Benefits

- Dual fuel compatible
- Wireless balance point for heat pumps
- Compatible with RS9055OUT Remote Sensor
- 7-day, 5-1-1 or non-programmable
- Large 8.8-square-inch blue backlit touchscreen display
- Auto changeover
- Adjustable temperature differential (swing)
- Senses outdoor temperature
- Use for dual fuel balance point applications
- Durable weatherproof design
- Compatible with RS9423T or RS10421T thermostat
- Wireless range from sensor to thermostat is 328 feet (100m)
- Battery powered (AA Batteries included)
- 1 year limited warranty

6 Year
Limited
Warranty

Robertshaw
RANCO • PARAGON • CASTFUTURA

Customer Service
+1 800 304 6563
HVACCustomerService
@robertshaw.com

Technical Service
+1 800 445 8299
TechnicalService
@robertshaw.com

www.robertshaw.com
©2024 Robertshaw
05/24 150-2909 RevB

Specifications

Dimensions (W x H x D)	4.7 x 3.8 x 1 in. (119.6 x 97.6 x 26 mm)
Mounting	Wall or junction box
System compatibility	Two-stage conventional heating and cooling or four-stage heating and two-stage cooling with heat pump
System fuel source	Gas, electric or oil
Heat pump compatibility	Systems without auxiliary or emergency heat
Millivolt application compatibility	Yes
Temperature range	32°F to 99°F (0°C to 40°C)
Control temperature range	41°F to 90°F (5°C to 32°C)
Display accuracy	±1°C (at 20°C) / ±1°F (at 68°F)
Power sources	24V AC (18 to 30V AC), 50/60 Hz for hardwire (common wire required) or 2 AAA 1.5V alkaline batteries (included)
Terminals	Rc, Rh, C, B, O, G, W/E, Y, Y2, W2

Replacement Information

RS9423T	
Pro1*	T755S
Honeywell	TH6320U2008
Braeburn*	4030, 4235
Copeland White-Rodgers™	1F85U-42PR

Optional Accessory Wireless Outdoor Temperature Sensor RS9055OUT

